

Ciao 1850

6÷24 ℓ - 1,1 kW








OILLESS





















Comandati tramite pressostato elettromeccanico, gruppo accessori con manometro e rubinetto rapido universale. Protezione da sovraccarico del motore elettrico.

They are commanded by electro-mechanical pressure switch, an accessory unit with manometer and a universal quick coupler. The electric motor features overload protection.

Die Steuerung erfolgt durch einen elektromechanischen Druckschalter, eine Zubehöreinheit mit Manometer und einer Schnelltrennkupplung. Der Elektromotor besitzt einen Überlastschutz.

Codice Code	Prodotto Product	 L x D x H (cm)	 kg	 Lbs	 tot.	 2101000010364951
626HOA1604	Ciao 6/1850	36 x 26 x 51	12,5	27,5	24	8017750219103
617HOA1604	Ciao 25/1850	60,5 x 24 x 56,5	20,5	45,1	18	8017750214856

 AIR	Codice Code	Prodotto Product	 Volt/Ph	 kW	 HP	 Model	 l/min.	 m ³ /h	 c.f.m.	 bar	 p.s.i.	 R.P.M.	 n°	 n°	 dB(A)	 LwA	 L x D x H (cm)	 kg	 Lbs
--	----------------	---------------------	---	--	---	--	--	---	--	---	--	--	--	--	---	---	--	--	---

SENZA OLIO MONOFASE 8 BAR | OILLESS SINGLE-PHASE 8 BAR | ÖLFREI EINPHASIG 8 BAR

6	626HOA1604	Ciao 6/1850	230/1	1,1	1,5	OL1850	179	10,7	6,3	8	116	2850	1	1	80	95	33 x 25,5 x 50	11,5	25,4
24	617HOA1604	Ciao 25/1850	230/1	1,1	1,5	OL1850	179	10,7	6,3	8	116	2850	1	1	80	95	58 x 27 x 60	19	41,9